PCT

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification [7] : **H04L 12/56, 12/28, H04M 7/00**	**A1**	(11) International Publication Number: **WO 00/35153**
		(43) International Publication Date: 15 June 2000 (15.06.00)

(21) International Application Number: PCT/US99/27400

(22) International Filing Date: 19 November 1999 (19.11.99)

(30) Priority Data:
60/110,972   4 December 1998 (04.12.98)   US
09/415,907   8 October 1999 (08.10.99)   US

(71) Applicant *(for all designated States except US)*: NORTEL NETWORKS CORPORATION [CA/CA]; World Trade Center of Montreal, 380 St. Antoine Street West, 8th floor, Montreal, Quebec H2Y 3Y4 (CA).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: BARANY, Peter [US/US]; 830 Hills Creek Drive, McKinney, TX 75070 (US). BHARATIA, Jayshree [IN/US]; 1717 Panigo Drive, Plano, TX 75075 (US).

(74) Agents: ANDERSON, Matthew, S. et al.; Felsman, Bradley, Vaden, Gunter & Dillon, L.L.P., 201 Main Street, Suite 1600, Fort Worth, TX 76102 (US).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published
With international search report.
Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: SYSTEM AND METHOD FOR IMPLEMENTING XoIP OVER ANSI–136–A CIRCUIT–SWITCHED/PACKET–SWITCHED MOBILE COMMUNICATIONS NETWORKS

(57) Abstract

The SS7 interface of a conventional GPRS–136 or GPRS–136HS network is replaced with an IP interface. An IP interface is placed between the ANSI TIA/EIA–41 circuit–switched network and the GPRS–136 packet–switched network. This interface can handle both signaling and bearer traffic and thereby overcomes the limitations imposed by the current SS7 interface, which can handle only signaling.

SYSTEM AND METHOD FOR IMPLEMENTING XoIP
OVER ANSI-136-A CIRCUIT-SWITCHED/PACKET-SWITCHED
MOBILE COMMUNICATIONS NETWORKS

Description

Technical Field

The present invention generally relates to improved mobile telecommunications systems and in particular to improved packet-switched wireless/wired communication systems. Still more particularly, the present invention relates to an improved packet-

5   switched telecommunications system which utilizes Internet Protocol packet communications.

Background Art

The written description utilizes a large number of acronyms to refer to

10   components, methods and services. Although these acronyms, and the corresponding protocols and technologies, are known to those of skill in the art, for purposes of this discussion and convenience for the reader, acronyms will be defined as follows:

15   AMPS   Advanced Mobile Phone Service. TIA analog cellular, and all standards that retain compatibility with it (NAMPS, D-AMPS, CDMA)

        ANSI   American National Standards Institute.

        BSS   Base Station System

20   DCCH   Digital Control Channel. The control channel used by IS-136 and TIA/EIA-136 D-AMPS systems.

        DTC   Digital Traffic Channel

        DMS   Digital Multiplex Switch

        EIA   Electronics Industry Association

25

        Gateway MSC   An MSC designed to provide a gateway between a TIA/EIA-136 / ANSI-41 network and a GPRS-136 network.

	GGSN	Gateway GPRS Support Node
	GPRS	Generalized Packet Radio Service. A GSM-based packet data protocol.
	GSM	Global System for Mobile Communications.
5	GTP	GPRS Tunnelling Protocol
	IMT	International Mobile Telecommunications
	ISUP	ISDN User Part. SS7 signaling between switches.
	MDIS	Mobile Data Interface System
	MGCP	Media Gateway Control Protocol
10	MSC	Mobile Switching Center
	MSC-G	Gateway MSC.
	MSC-H	Home MSC.
	MSC-O	Originating MSC.
	MSC-V	Visited MSC. The MSC in which a mobile is currently registered.
15	PDN	Public Data Network
	POTS	Plain Old Telephone Service
	PSTN	Public Switched Telephone Network
	Protocol	A specification of the messages used to communicate over one or more interfaces.
20	RTP	Real-Time Transport Protocol
	SCP	Signal Control Point
	SGSN	Serving GPRS Support Node
	STP	Signal Transfer Point
	SS7	Signaling System Number 7
25	TDMA	Time Division Multiple Access. A modulation technique used, e.g., by GSM.
	TIA	Telecommunications Industry Association
	TIA/EIA-136	TDMA air interface standard. Replaces IS-136.
	XoIP	Communications via Internet Protocol, where X can represent
30		voice, data, video, etc.

- 3 -

In the current version of the ANSI TIA/EIA-136 and ANSI TIA/EIA-41 standards, the Digital Control Channel (DCCH) and Digital Traffic Channel (DTC) support speech, asynchronous circuit-switched data, and G3 Fax services.

5   All three of these services are circuit-switched oriented. Revisions are now being made to the ANSI TIA/EIA-136 standard to produce ANSI TIA/EIA-136-A and ANSI TIA/EIA-136-B. ANSI TIA/EIA-136-A will specify a packet-switched data service known as "136+"or GPRS-136. ANSI TIA/EIA-136-B will specify a high-speed packet-switched service known as "136HS" or GPRS-136HS. The core
10   technology for both of these packet-switched services is based on GPRS and EGPRS, respectively. These are ETSI GSM standards.

          Figure 1 shows a conventional GPRS-136-based network where voice and circuit-switched data is still supported by the circuit switched network 103/104 but
15   packet-switched data is supported by the GPRS-136 packet data network 106. Gateway MSC (G-MSC) 103 is a new functional entity standardized for GPRS-136, which is an MSC having the capability to provide a gateway to GPRS-136 network. Hence, G-MSC can be viewed as a part of MSC or a separate network Node. If it is considered a separate node, the SS7 'E' interface is used to exchange signaling
20   messages with MSC.

          In Figure 1, a mobile station MSx 101, which incorporates a vocoder and handles voice or circuit-switched data calls, communicates over the air with a BSSx switch 102, which supports voice and/or circuit switched data. The BSSx 102
25   communicates via both a T1 bearer traffic interface and a signaling interface A with a gateway mobile switching center 103. The SS7 network 104 is connected, in turn, with a terminating network 105 and a GPRS-136 network 106. Note that connection Gs', between the SS7 network 104 and the GPRS-136 network 106, is a signaling interface only.

30

- 4 -

A GPRS-136 mobile station MSy **107**, also incorporating a vocoder and configured to support voice and/or packet-switched data, communicates over the air with a BSSy switch **108**, which supports packet data. The BSSy **108** communicates over a bearer traffic interface **Gb'** with the GPRS-136 network **106**. For voice calls,

5   the vocoder of MSy **107** communicates with the BSSx switch **102**, as described above.

GPRS-136 network **106** is connected to Public Data Network (PDN) **109**. The PDN includes any destination terminal equipment **110**.

10

TDMA service operators have expressed a desire to implement XoIP over the GPRS-136 network (where X can represent voice, data, video, etc., *e.g.*, VoIP). XoIP can be implemented over the circuit-switched or packet-switched air interface. However, the current interface Gs' to the GPRS-136 packet-switched network is

15   standardized for signaling only and is implemented via SS7. Therefore, if the circuit-switched air interface is to be used, this is a problem, because XoIP involves the transmission of both signaling and bearer traffic. Therefore, the SS7 interface is inappropriate and an XoIP solution utilizing the GPRS-136 network would be greatly desired.

20

Disclosure of Invention

It is therefore one object of the present invention to provide an improved mobile telecommunications system.

25   It is another object of the present invention to provide an improved packet-switched mobile telecommunications system.

It is yet another object of the present invention to provide an improved packet-switched telecommunications system which utilizes Internet Protocol packet

30   communications.

The foregoing objects are achieved as is now described. According to the preferred embodiment of the invention, the SS7 interface of a conventional GPRS-136 network is replaced with an IP interface. In this embodiment. an IP interface is placed in parallel with the Gs' interface between the DMS MSC/G-MSC and the

5   GPRS-136 packet-switched network. This interface can handle both signaling and bearer traffic and thereby overcomes the limitations imposed by the current SS7 interface, which can handle only signaling.

The above as well as additional objectives, features, and advantages of the

10   present invention will become apparent in the following detailed written description.

Brief Description of Drawings

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself however, as well as a preferred mode of use,

15   further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with August 18, 1999the accompanying drawings, wherein:

Figure 1 depicts a conventional GPRS network;

20

Figure 2 is an improved GPRS/IP network, in accordance with a preferred embodiment of the invention;

Figure 3 shows a diagram of the delivery of a telephone call or circuit-switched

25   data transaction originating in an ANSI-136-A voice or circuit-switched data mobile station to an IP network, in accordance with a preferred embodiment of the invention;

Figure 4 shows a diagram of the delivery of a telephone call or circuit-switched

30   data transaction originating in an ANSI-136-A voice or circuit-switched data mobile

- 6 -

station to another ANSI-136/ANSI-41 network (or vice versa) via an IP network, in accordance with a preferred embodiment of the invention; and

5   **Figure 5** shows a diagram of the delivery of a telephone call or circuit-switched data transaction originating in an ANSI-136-A voice or circuit-switched data mobile station to a Circuit-Switched Network (SCN) such as PSTN, ISDN via an IP network, in accordance with a preferred embodiment of the invention.

Best Mode for Carrying Out the Invention

10   With reference now to the figures, and in particular with reference to **Figure 2**, according to the preferred embodiment, the GS' interface of the conventional GPRS-136 network is improved to support bearer data and call control signaling in addition to existing signaling. The improved GS' interface also replaces transport of this interface from SS7 with IP. Further, the preferred embodiment bypasses the

15   vocoder which currently is required by the G-MSC/MSC. It should be noted that where "GPRS-136" is used below, it is intended to apply to the entire GPRS-136 "family", including GPRS, EGPRS, GPRS-136, and GPRS-136HS. Further, those of skill in the art will recognize that the innovative system and techniques described below will also apply to other wireless standards and technologies.

20

The preferred embodiment is thus a great improvement over the conventional GPRS-136 network shown in **Figure 1**, in which the current interface (Gs') between the Gateway MSC (G-MSC) and SGSN node of packet data network is standardized for signaling only and is implemented via SS7.

25

As shown in **Figure 2**, a new functional node, also known as PSTN gateway **212**, is defined between the traditional network and the IP network **211**. Different interfaces of the PSTN gateway are currently being standardized in IETF (Internet Engineering Task Force), and specific implementations are within the ability of one

30   of ordinary skill in the art. A standard device control protocol can be used between its three functional entities, the Media Gateway, (MG) the Media Gateway Controller

- 7 -

(MGC), and Call Agent (CA) or Signaling Gateway (SG). In all figures, CA is assumed to support the functionality of MGC.

5   According to the preferred embodiment, there is no change in the way voice is handled, from an access point of view, i.e., there are no changes required at BSS or Mobile. Signaling for a voice call is still handled by A interface and bearer is transported using T1 links.

10   With reference to **Figure 2**, voice and circuit-switched data is still supported by the circuit switched network **203/204** and packet-switched data is supported by the GPRS-136 packet data network **206**. Gateway MSC (G-MSC) **203** provides a gateway to GPRS-136 network.

15   In **Figure 2**, a mobile station MSx **201**, which can incorporate a vocoder and handles voice or circuit-switched data calls, communicates over the air with a BSSx switch **202**, which supports voice and/or circuit switched data. The BSSx **202** communicates via both a T1 bearer traffic interface and a signaling interface A with a gateway mobile switching center **203**. The SS7 network **204** is connected, in turn, with a GPRS-136 network **206**. Note that connection **Gs'**, between the SS7
20   network **204** and the GPRS-136 network **206**, is a signaling interface only.

       A GPRS-136 mobile station MSy **207**, also incorporating a vocoder and configured to support voice and/or packet-switched data, communicates over the air with a BSSy switch **208**, which supports packet data. The BSSy **208** communicates
25   over a bearer traffic interface **Gb'** with the GPRS-136 network **206**. For voice calls, the vocoder of MSy **207** communicates with the BSSx switch **202**, as described above.

       GPRS-136 network **206** is connected to PDN/IP network **214**. The PDN/IP
30   network **214** is connected to terminating network **215**.

- 8 -

According to the preferred embodiment, for outgoing calls, the signaling data is sent to Call Agent **212** from SS7 network **204** and bearer data is sent to MG **213** from DMS MSC/G-MSC **203**. The MG **213** of this gateway converts media (voice etc.) appropriately. These media packets are sent to SGSN of GPRS-136 network

5   **206** via **Gs'ip** interface. Within the GPRS-136 network **206**, packets are passed to GGSN, and then the packets are passed to PDN/IP network **214** and terminating network **215**, as it has been done for data packets in conventional systems.

For incoming calls, all packets are received by the GGSN from the PDN/IP

10   network **214**, and then are passed to SGSN via GTP. Until this point, the processing of the packets is as done in a conventional GPRS system as in **Figure 1**. In the preferred embodiment, however, instead of just passing this information to BSS, **SGSN** will distribute packets received and forward non-data related packets to the PSTN gateway **213** via **Gs'ip** interface. The MG **213** converts these packets and

15   sends information over T1 links to BSS. Similarly, signaling packets from **SGSN** are received over **Gs'ip** interface and get converted at Call Agent **212** and sent over the 'A' interface. It should be noted that the conversion of data between the different type of subnetworks may be done by any current method, and is well within the ability of one of ordinary skill in the art.

20

Note that in both these cases, the vocoder is bypassed. Also, the Terminating Network **215** shown in **Figure 2** can be a Wireless Network, PSTN, or other compatible system.

25   In these figures, as in **Figure 1**, above, where Terminal Specific Signaling is indicated, the following designations apply:

H.323	= >	H.225 and Q.931
SIP	= >	SAP, SIP or RTSP
BSSx	= >	Supports Voice and/or Circuit-Switched Data
BSSy	= >	Supports Packet Data

30

MSx   = >   A Mobile Station which Supports Voice and/or Circuit-
                   Switched Data

MSy   = >   A Mobile Station which Supports Packet-Switched Data

5   Further, solid lines are used to indicate a bearer traffic interface, dashed lines
are used to indicate a signaling interface, and a dot/dash line is used to indicate a
new bearer traffic and signaling interface according to the preferred embodiment.

10   **Figures 3-5** are exemplary illustrations of different transactions made over a
system as shown in the preferred embodiment of **Figure 2**. **Figure 3** shows a
diagram of the delivery of a telephone call or circuit-switched data transaction
originating in an ANSI-136-A voice or circuit-switched data mobile station to an IP
network or vice versa. Here, the call is routed as described above with relation to
Figure 2, where the IP network **314**, instead of passing data to a terminating
15   network (as **214** in **Figure 2**), simply routes the data via IP protocol to the remote IP
end system **316** and/or to an H.323 terminal **317**.

             Figure 4 shows a diagram of the delivery of a telephone call or circuit-switched
data transaction originating in an ANSI-136-A voice or circuit-switched data mobile
20   station to another ANSI-136/ANSI-41 network (or vice versa) via an IP network.
Here, the call is routed as described above with relation to **Figure 2**, where the
terminating network is an ANSI-136/ANSI-41 network. After the call is routed to
PSTN Gateway **423** from the GGSN of GPRS-136 network **406**, it is passed over an
SS7 network **418**/PSTN **419** to the ANSI-136 mobile switching center **420**. From
25   here, it is passed over the **A** interface and T1 to the BSSx **421**, and over the air to
the ANSI -136 mobile station MSx **422**.

             Figure 5 shows a diagram of the delivery of a telephone call or circuit-switched
data transaction originating in an ANSI-136-A voice or circuit-switched data mobile
30   station to a Circuit-Switched Network (SCN) such as PSTN, ISDN via an IP network.
Here, the call is routed as described above with relation to **Figure 2**, where the

- 10 -

terminating network is a PSTN. After the call is routed to PSTN Gateway **525** from the GGSN of the GPRS-136 network **506**, it is passed to the PSTN **519**, then to a standard POTS switch **523** and telephone **524**.

5   While the invention has been particularly shown and described with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the invention.

Claims

1.   A communications network, comprising:

a circuit-switched communications subnetwork;

a packet-switched subnetwork,

5   a Internet Protocol-based communications subnetwork, connected to send and receive data between the circuit-switched subnetwork and the packet-switched subnetwork; and

wherein the Internet Protocol-based subnetwork communicates both signal and bearer traffic for voice and data communications.

10

2.   The network of claim 1, wherein the circuit-switched subnetwork includes an SS7 network.

3.   The network of claim 1, wherein the packet-switched subnetwork includes a
15   GPRS-136 network.

4.   The network of claim 1, wherein the packet-switched subnetwork includes a GPRS-136HS network.

20   5.   The network of claim 1, wherein the packet-switched subnetwork includes a EGPRS network.

6.   The network of claim 1, further comprising a second Internet Protocol-based communications subnetwork connected to send and receive data from the packet-
25   switched subnetwork.

7.   The network of claim 1, further comprising a second circuit-switched subnetwork connected to send and receive data from the Internet Protocol-based subnetwork.

30

- 12 -

8.   The network of claim 1, further comprising a public service telephone network connected to send and receive data from the packet-switched subnetwork.

9.   The network of claim 1, wherein the circuit-switched subnetwork is configured
5   to send and receive data from a wireless station.

10.   The network of claim 1, wherein the circuit-switched subnetwork is configured to send and receive voice communications from a wireless station.

10   11.   A method for communicating between electronic devices, comprising:
        receiving a first data, from a mobile station, in a circuit-switched network;
        converting the first data in to a second data, said second data being comprised
of multiple data packets;
        sending the second data over an Internet Protocol-based network;
15   receiving the second data in a packet-switched network; and
        sending the second data to a terminating network.

12.   The method of claim 11, wherein the circuit-switched subnetwork includes an SS7 network.
20

13.   The method of claim 11, wherein the packet-switched subnetwork includes a GPRS-136 network.

14.   The method of claim 11, wherein the packet-switched subnetwork includes
25   a GPRS-136HS network.

15.   The method of claim 11, wherein the packet-switched subnetwork includes a EGPRS network.

30   16.   The method of claim 11, wherein the terminating network includes a second Internet Protocol-based communications subnetwork.

17.   The method of claim 11, wherein the terminating network includes a second circuit-switched subnetwork.

18.   The method of claim 11, wherein the terminating network includes a public service telephone network.

19.   The method of claim 11, wherein the circuit-switched subnetwork communicates with the mobile station by wireless communications.

20.   The method of claim 11, wherein the circuit-switched subnetwork is configured to send and receive voice communications from the mobile station.

1/5

Fig. 1

Fig. 2

Remote IP End System — 316

H.323 Terminal — 317

IP Network — 314

PSTN Gateway 311

Device Control Protocol

Call Agent — 313

Media Gateway

IP Network

ISUP

IMT — 303

Gs' IP

[RTP]

SS7 Network — 304

STP

DMS-MSC/G-MSC

Vocoder

A

T1

BSSx — 302

Gs'

Gb'

BSSy — 308

GGSN

[GTP]

GPRS-136 Network

SGSN

306

Packets

Packets

air

air

MSx — 301

MSy — 307

Fig. 3

Fig. 4

5/5

Fig. 5

INTERNATIONAL SEARCH REPORT

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7   H04L12/56   H04L12/28   H04M7/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7   H04L   H04M   H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 742 905 A (BROCKMAN JAMES JOSEPH ET AL) 21 April 1998 (1998-04-21) column 1, line 11 - line 43; figure 3 column 5, line 28 -column 6, line 10 column 24, line 31 -column 25, line 30 ---	1-20
X	WO 97 16007 A (SAKSANEN PAULI ;FINLAND TELECOM OY (FI); KARHAPAEAE TUOMO (FI)) 1 May 1997 (1997-05-01) page 3, line 21 -page 4, line 23 page 5, line 22 -page 6, line 9 page 10, line 31 -page 12, line 32 ---	1-20
A	WO 98 19438 A (ERICSSON TELEFON AB L M) 7 May 1998 (1998-05-07) page 8, line 3 -page 9, line 28; figure 1 ---	3-5, 13-15

-/--

[X] Further documents are listed In the continuation of box C.   [X]   Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance
"E" earlier document but published on or after the international filing date
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
"O" document referring to an oral disclosure, use, exhibition or other means
"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
2 May 2000	15/05/2000

Name and mailing address of the ISA	Authorized officer
European Patent Office, P.B. 5818 Patentlaan 2 NL – 2280 HV Rijswijk Tel. (+31–70) 340–2040, Tx. 31 651 epo nl, Fax: (+31–70) 340–3016	Brichau, G

Form PCT/ISA/210 (second sheet) (July 1992)

page 1 of 2

INTERNATIONAL SEARCH REPORT

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication,where appropriate, of the relevant passages	Relevant to claim No.
A	WO 98 44701 A (ERICSSON TELEFON AB L M) 8 October 1998 (1998-10-08) page 6, line 20 -page 7, line 10; figure 1 page 8, line 17 -page 9, line 24	1,11

3

INTERNATIONAL SEARCH REPORT

Information on patent family members

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 5742905	A	21-04-1998	CA	2199802 A	28-03-1996
			EP	0782805 A	09-07-1997
			JP	9511884 T	25-11-1997
			WO	9609714 A	28-03-1996
			US	5742668 A	21-04-1998
WO 9716007	A	01-05-1997	AU	7302596 A	15-05-1997
			FI	955810 A	26-04-1997
WO 9819438	A	07-05-1998	SE	510664 C	14-06-1999
			AU	4888897 A	22-05-1998
			BR	9712387 A	31-08-1999
			CN	1235727 A	17-11-1999
			EP	0928535 A	14-07-1999
			SE	9603948 A	30-04-1998
WO 9844701	A	08-10-1998	AU	6934798 A	22-10-1998
			EP	0972393 A	19-01-2000
			NO	994222 A	30-11-1999